

Fitting instruction
Montageanleitung
Monteringsvejledning
Monteringsvægledning
Montage hanleiding
Manuel de montage



T60:



T68:



T65:



1

T60

28 mm
1 1/8"

55 mm
2 1/8"

Ø17 mm
Ø11/16"

290 mm
11 3/8"

1500 mm
5'

G1/2"

Ø60 mm
Ø2 3/8"

Service - VR556

✓

✗

Bathtub
Badewanne

Badekar
Badkar

Badkuip
Baignoire

T68

Min. 350 mm
Min. 14"

070

Min. 200 mm
Min. 8"

40 mm
1 5/8"

✗

✓

2

T68

Ø43 mm
Ø1 3/4"

40 mm
1 5/8"

SILICONE

Ø6 mm
1/4"

25 mm
1"

001G

3

T65

50 mm
2"

55 mm
2 1/8"

Ø60 mm
Ø2 3/8"

790 mm
31"

690 mm
27 1/8"

590 mm
23 1/4"

490 mm
19 1/4"

900 mm
35 3/8"

800 mm
31 1/2"

700 mm
27 1/2"



600 mm
23 5/8"

1




Data	Bar:	1	2	3	4	5
T60	(l/min) (Gal/min)	6.9 1.8	9.8 2.6	12 3.2	14 3.7	15 4.1
	Max. 65°C. 150°F					

USA:
Max. flow rate:
1.6 Gal/min
6.0 l/min.


4

490 mm
19 1/4"590 mm
23 1/4"690 mm
27 1/8"790 mm
31"




5

24 - 42 mm
1" - 1 3/4"Ø54 mm
Ø2 1/8"

Ø4 mm



6

490 mm
19 1/4"590 mm
23 1/4"690 mm
27 1/8"790 mm
31"

Alt.:

180°


7



8



Ø2 mm



vola
 Lunavej 2
 DK-8700 Horsens
 Tlf : + 45 7023 5500
 Fax: + 45 7023 5511
 sales@vola.com
 www.vola.com

VOLA T68

Date
 Mar. 15

Rev.
 0

Sheet
SB 42.68