

Fecha:

Cliente:

Proyecto:



Mezclador monomando sobre encimera con válvula cerámica 500, caño giratorio 090A con aireador para el ahorro de agua. Altura de 110 mm. Orificio mezclador: 42 mm. Orificio caño: 22 mm.

	Bar:	1,0	2,0	3,0	4,0	5,0
590A ¹⁾	(l/min)	2,3	3,3	4,0	4,0	4,0
590A	(l/min)	4,8	6,8	8,3	8,3	8,3

Technical drawing of the 1000 Series Cable Management System, showing side and top views with dimensions.

Side View Dimensions:

- Overall height: 110 mm (4 1/4")
- Top flange thickness: 40 mm (1 1/2")
- Top flange width: 85 mm (3 1/2")
- Top flange width: 78 mm (3 1/16")
- Maximum cable diameter: Max 700 mm (Max 28")
- Top flange hole diameter: Ø19 mm (Ø3/4")
- Top flange hole diameter: Ø60 mm (Ø2 3/8")
- Top flange hole diameter: Ø40 mm (Ø1 5/8")
- Top flange hole diameter: Ø42 mm (Ø1 5/8")
- Top flange hole diameter: US: 9/16"
- Top flange hole diameter: G3/8"
- Top flange hole diameter: 19"
- Top flange hole diameter: 480 mm
- Top flange hole diameter: 1/2"
- Top flange hole diameter: 300 mm (12")

Top View Dimensions:

- Top flange hole diameter: Ø22 mm (Ø7/8")
- Top flange hole diameter: Ø42 mm (Ø1 5/8")
- Top flange hole diameter: US: 9/16"
- Top flange hole diameter: G3/8"
- Top flange hole diameter: 19"
- Top flange hole diameter: 480 mm
- Top flange hole diameter: 1/2"
- Top flange hole diameter: 300 mm (12")

02 Gris	25 Rosa
04 Azul claro	27 Negro mate
05 Naranja	28 Blanco mate
06 Verde claro	60 Negro
08 Amarillo	61 Negro cepillado
09 Gris oscuro	62 Negro profundo
12 Mocca	63 Cobre
14 Rojo brillante	64 Cobre cepillado
15 Azul oscuro	65 Oro
17 Negro gloss	70 Oro cepillado
18 Blanco	Acero inoxidable cepillado
19 Latón natural	Color 68, Plata
20 Cromo cepillado	Cromo
21 Rojo carmin	



Technical drawing of the U-bolter assembly with dimensions:

- Overall height: 110 mm (4 1/4")
- Top flange width: 85 mm (3 1/2")
- Top flange thickness: 40 mm (1 1/2")
- Top flange outer diameter: Ø19 mm (Ø3/4")
- Top flange inner diameter: Ø40 mm (Ø1 5/8")
- Max height of U-bolter: Max 55 mm (Max 2 1/8")
- Max height of base plate: Max 65 mm (Max 2 1/2")
- Base plate thickness: 1/2"
- Drill bit dimensions: Ø22 mm / Ø7/8"



Technical drawing of the 3-Phase 480V 3-Wire Grounded Cable Adapter. The drawing shows a top view and a side view. The top view shows a circular base with a central hole of diameter Ø42 mm (1 5/8 inches) and an outer diameter of Ø60 mm (2 3/8 inches). The base has a thickness of 19 mm (3/4 inch). The side view shows the adapter's profile, with a maximum height of 45 mm (1 3/4 inches) and a maximum width of 480 mm (19 inches). The adapter is designed to connect a 3-phase 480V 3-wire grounded cable to a 3-phase 480V 3-wire grounded cable. The cable has a diameter of Ø40 mm (1 5/8 inches) and a length of 480 mm (19 inches). The cable is shown with a braided shield and a central conductor. The adapter is shown with a 3/8 inch (9/16 inch US) threaded hole. A 3/4 inch (1 5/8 inch) hole is also shown.